



# DUNBAR – EV2500

2:1 SHRINK RATIO, HIGH VOLTAGE, VERY FLEXIBLE, V-O FLAMMABILITY, EV TUBING

## Applications

DUNBAR-EV2500 is a flexible, flame retardant (V-O), heat shrinkable Modified Polyolefin tube for applications requiring outstanding high voltage and V-O flammability standards. It reliably protects wires, solder joints, terminals, connections, and components.

## Features

- Shrink ratio: 50% or more in the radial direction, 5% or less in the axial direction
- Operating Voltage (Max) 2.5kV
- Continuous operating temperature: -55°C (-67°F) to 135°C (275°F)
- Flammability: UL V-O
- Very Flexible
- Min. Shrink Temp 70°C
- Standard Color EV Orange

## Standards

- UL 224: V-O Tested Internally
- Declared Dimensional Life (DDL) – 3 Years
- RoHS & REACH Compliant

## Specification Values

Property		Test Standard	Value	
Physical	Unaged	Tensile strength	UL 224	Min. 1,500 psi
		Elongation		Min. 200%
	Aged	Tensile strength	UL 224 158°C x 168 hrs	Min. 1,000 psi
		Elongation		Min. 100%
	Heat shock		UL 224	No cracks, flowing or dripping
Cold Bend		-30°C x 1 hr	No cracking	
Electrical	Dielectric Withstand	300V	1500V 1 min	Without breakdown
		600V	2500V 1 min	Without breakdown
	Dielectric strength		UL 224	15kV/mm min.
	Volume resistivity		UL 224	Min. 10 <sup>14</sup> Ω * cm
Chemical	Copper stability		158°C x 168 hrs	No corrosion
	Anti Corrosion		UL 224	Pass
	Flammability		UL 94 V-O	Pass

Rev. August 2023




Dunbar Products, LLC  
Tubing and Identification Products

1302 Champion Circle, Carrollton, TX 75006  
Tel: (469) 568-0800  
Fax: (469) 568-0808



# DUNBAR – EV2500

2:1 SHRINK RATIO, HIGH VOLTAGE, VERY FLEXIBLE, V-O FLAMMABILITY, EV TUBING



## Product Dimensions

Minimum Shrink Temperature: 70°C

Size	IEWC Part Number	Expanded		Recovered				Standard Spool Length
		Internal Diameter (Minimum) (D)		Internal Diameter (Maximum) (d)		Nominal Wall Thickness (t)		
		In.	mm	In.	mm	In.	mm	
mm								Ft.
10/5	32185367	0.394	10.0	0.177	4.5	0.025	0.64	200 ft.
12.7/6.4	32185398	0.500	12.7	0.252	6.4	0.025	0.64	200 ft.
20/9.5	32185401	0.787	20.0	0.374	9.5	0.030	0.76	100 ft.
26/12.7	32185403	1.024	26.0	0.500	12.7	0.035	0.88	100 ft.
40/19	32185404	1.575	40.0	0.748	19.0	0.040	1.01	100 ft.
50/25	32185405	1.969	50.0	0.984	25.0	0.045	1.14	100 ft.

Standard Colors: Orange  
 Optional Color(s): Available by special order

Rev. August 2023



**Dunbar Products, LLC**  
 Tubing and Identification Products

1302 Champion Circle, Carrollton, TX 75006  
 Tel: (469) 568-0800  
 Fax: (469) 568-0808