



Wall Mount Distribution Panel
Ordering Information
(fiber splicing applications)

- Steel housing with black powder coat finish
- Enclosure thickness: 16 Gauge



2 Plate Configuration



4 Plate Configuration

Fiber Capacity	Dimensions
1 adapter plate, 6-12 capacity	7"W x 1.5"D x 6.5"H
2 adapter plates, 12-24 capacity	15.625"W x 2.125"D x 13"H
4 adapter plates, 24-48 capacity	15.625"W x 3.5"D x 15"H
8 adapter plates, 48-96 capacity	12.25"W x 6"D x 17"H

343



Loaded Ports

- 0 = 0
- 12 = 1
- 24 = 2
- 48 = 4
- 72 = 6
- 96 = 7

- Panel Size**
- 1 Plate
 - 2 Plates
 - 4 Plates
 - 8 Plates

- Wall Mount**
- Distribution

- Cable Exit**
Terminated Into Splice Tray B
No Pigtail 0

- Pigtail Type**
- No Pigtail 0
 - SM UPC Polish 2
 - SM APC Polish 3
 - MM 50/125 Fiber 4
 - MM 62.5/125 Fiber 5
 - MM 100/140 Fiber 6

Cable Length

Specify in feet if pigtail is used. If not, populate with 000. ex. (005 = 5 Feet), (000 = No Pigtail)

Cable Type

- No Pigtail 0
- 3' 900um Breakout 1
- 2.0mm Simplex Pigtails 2
- 12-Fiber 3' 900um Breakout 3

Connector/Adapter Style

- SM SC Simplex UPC Polish 01
- SM SC Duplex UPC Polish 02
- SM FC Simplex D-Hole UPC Polish 04
- SM FC Simplex D-Hole APC Polish 05
- SM ST Metal Simplex UPC Polish 13
- MM SC Simplex PC Polish 07
- MM SC Duplex PC Polish 08
- MM FC Simplex D-Hole PC Polish 10
- SM SC Simplex APC Polish 11
- SM SC Duplex APC Polish 12
- SM ST 12-Port (High Density) UPC Polish 06
- SM LC Duplex UPC Polish 15
- SM LC Duplex APC Polish 17
- SM LC Quad (High Density) UPC Polish 29
- SM MPO Rear/LC Front UPC Polish 18
- SM MPO Rear/LC Front APC Polish 19
- SM MPO Rear/SC Front UPC Polish 20
- SM MPO Rear/SC Front APC Polish 21
- MM 62.5 MPO Rear/LC Front PC Polish 22
- MM 62.5 MPO Rear/SC Front PC Polish 23
- MM 62.5 MPO Rear/ST Front PC Polish 24
- MM 50 micron MPO Rear/LC Front PC Polish 25
- MM 50 micron MPO Rear/SC Front PC Polish 26
- MM 50 micron MPO Rear/ST Front PC Polish 27

Splice Pad

- No Pigtail 0
- Fusion Splice 1
- Fusion Splice w/Heat Shrink 2
- Mechanical 3

Simplex Ports = 6 Connectors Per Plate
Duplex Ports = 12 Connectors Per Plate
Quad Ports = 24 Connectors Per Plate

DALLAS • DETROIT

Corporate Offices: 359 Robbins Drive • Troy, MI 48083
Phone: 888.8.CABLCON • Fax: 248.588.1462 • www.cablcon.com

